APOLLO L

view

RAL

size

1 overall dimensions

1









APOLLO L

Pendant street lighting for mounting on the tensioned metal cable in parks, streets and city areas with the wide range of light distribution types.

Housing:	Pressure die-cast aluminum alloy with polyester powder paint.
Beam angle:	150x75, 145x130, 150x105, 160x60, 150x70, 155x55, 120x15
Housing color:	Black, Grey, RAL
Color temperature, K:	3000K - 5000K
Color rendering index, CRI:	>70
IK:	10
Power factor:	>0.9
Control system:	Switch On\Off
Input voltage, V:	220V
Ingress Protection Rating, IP:	IP66
Operating temperature:	-40°C to +50°C
Guaranteed lifetime, hours:	>75 000h

Article	Name	Power, W	Dimensions, mm	Input voltage, V	Beam angle, degrees	Color Temperature, K	Weight, kg
754040030	APOLLO L 40W 220V IP66	40W	550x490x161	220V	150x75°, 145x130°, 150x105°, 160x60°, 150x70°, 155x55°, 120x15°	3000K-5000K	10kg
754055030	APOLLO L 55W 220V IP66	55W	550x490x161	220V	150x75°, 145x130°, 150x105°, 160x60°, 150x70°, 155x55°, 120x15°	3000K-5000K	10kg
754070030	APOLLO L 70W 220V IP66	70W	550x490x161	220V	150x75°, 145x130°, 150x105°, 160x60°, 150x70°, 155x55°, 120x15°	3000K-5000K	10kg
754110030	APOLLO L 100W 220V IP66	110W	550x490x161	220V	150x75°, 145x130°, 150x105°, 160x60°, 150x70°, 155x55°, 120x15°	3000K-5000K	10kg
754150030	APOLLO L 150W 220V IP66	150W	550x490x161	220V	150x75°, 145x130°, 150x105°, 160x60°, 150x70°, 155x55°, 120x15°	3000K-5000K	10kg
754040040	APOLLO L clip 40W 220V IP66	40W	550x490x200	220V	150x75°, 145x130°, 150x105°, 160x60°, 150x70°, 155x55°, 120x15°	3000K-5000K	10kg
754055040	APOLLO L clip 55W 220V IP66	55W	550x490x200	220V	150x75°, 145x130°, 150x105°, 160x60°, 150x70°, 155x55°, 120x15°	3000K-5000K	10kg
754070040	APOLLO L clip 70W 220V IP66	70W	550x490x200	220V	150x75°, 145x130°, 150x105°, 160x60°, 150x70°, 155x55°, 120x15°	3000K-5000K	10kg
754110040	APOLLO L clip 100W 220V IP66	110W	550x490x200	220V	150x75°, 145x130°, 150x105°, 160x60°, 150x70°, 155x55°, 120x15°	3000K-5000K	10kg
754150040	APOLLO L clip 150W 220V IP66	150W	550x490x200	220V	150x75°, 145x130°, 150x105°, 160x60°, 150x70°, 155x55°, 120x15°	3000K-5000K	10kg