

view



size

1 AMANTA SPOT (S)


2 AMANTA SPOT (M)

AMANTA SPOT (S)






AMANTA SPOT (M)

1



2



AMANTA

Railing recessed luminaire

Housing:	Sealed molded housing
Housing color:	Metallic
Beam angle:	15°, 30°, 60°, Asy 50°, Asy 70°
Color temperature, K:	2700K, 3000K, 4000K, R, G, B, RGB, RGBW
Input voltage, V:	12V, 24V
Control system:	DMX-512, Switch On/Off
Ingress Protection Rating, IP:	IP67
Operating temperature:	-40°C ~ +50°C
Weight:	0,1-0,2kg

Article	Name	Power, W	Dimensions, mm	Input voltage, V	Beam angle, degrees	Color temperature, K	Weight, kg
692200010	AMANTA SPOT (S) 1W IP67	1W	D18x20	12V, 24V	15°, 30°, 60°	2700K, 3000K, 4000K, R, G, B	0,10
692200012	AMANTA SPOT (S) 1,5W IP67	1,5W	D18x20	12V, 24V	15°, 30°, 60°	2700K, 3000K, 4000K, R, G, B	0,10
692200014	AMANTA SPOT (S) 1,2W IP67	1,2W	D18x20	12V, 24V	Asy 50°	2700K, 3000K, 4000K, R, G, B	0,10
692200016	AMANTA SPOT (M) 1,5W IP67	1,5W	D29x30,5	12V, 24V	60°	2700K, 3000K, 4000K, R, G, B	0,20
692200018	AMANTA SPOT (M) 1,5W RGBW IP67	1,5W	D29x30,5	12V, 24V	26°, 60°	RGBW	0,20
692200020	AMANTA SPOT (M) 2W RGB DMX-512 IP67	2W	D29x30,5	12V, 24V	60°, Asy 70°	RGB	0,20