

GLORA TRIMLESS









view



size

- 1 2W
- 2 4W
- 3 5W
- 4 7W
- 5 10W
- 6 15W



GLORA TRIMLESS

In-ground luminaires featuring a durable tempered glass face cover

Housing:	Die-casting aluminum, stainless steel
Beam angle:	5°, 10°, 12°, 15°, 20°, 24°, 30°, 36°, 40°, 55°, 60°, 10°×45°, 25°×45°
Housing color:	Black
IES protection classes:	Class I, III (SELV)
Color temperature:	2700K, 3000K, 4000K, 5000K, 6000K, 6500K
Input voltage:	12/24V, 220V
Control system:	On/Off
Ingress Protection Rating:	IP67
Operating temperature:	-40°C ~ +50°C
Weight, kg:	0.08 - 1 kg

Article	Name	Power, W	Dimensions, mm	Input voltage, V	Beam angle, degrees	Color temperature, K	Weight, kg
793002040	GLORA TRIMLESS 2W 12V/24V IP67 SINGLE D32	2W	Ø32×58	12 V, 24V	5°, 10°, 15°, 20°, 30°, 40°, 60°, 10°×45°, 25°×45°	2700K, 3000K, 4000K, 5000K, 6000K, 6500K	0.08
793002042	GLORA TRIMLESS 4W 12V/24V/220V IP67 SINGLE D42	4W	Ø42×76	12 V, 24V, 220 V	15°, 24°, 36°, 55°	2700K, 3000K, 4000K, 5000K, 6000K, 6500K	0.15
793002044	GLORA TRIMLESS 5W 12V/24V/220V IP67 SINGLE D50	5W	Ø50×75	12 V, 24V, 220 V	12°, 24°, 36°, 55°	2700K, 3000K, 4000K, 5000K, 6000K, 6500K	0.25
793002046	GLORA TRIMLESS 7W 12V/24V/220V IP67 SINGLE D65	7W	Ø65×89	12 V, 24V, 220 V	12°, 24°, 36°, 55°	2700K, 3000K, 4000K, 5000K, 6000K, 6500K	0.3
793002048	GLORA TRIMLESS 10W 12V/24V/220V IP67 SINGLE D80	10W	Ø80×99	12 V, 24V, 220 V	12°, 24°, 36°, 55°	2700K, 3000K, 4000K, 5000K, 6000K, 6500K	0.6
793002050	GLORA TRIMLESS 15W 12V/24V/220V IP67 SINGLE D100	15W	Ø100×115	12 V, 24V, 220 V	12°, 24°, 36°, 55°	2700K, 3000K, 4000K, 5000K, 6000K, 6500K	1