

GLOWHEAD XXL



view




RAL




size

1 overall dimensions



1



GLOWHEAD XXL

Multifunctional floodlight with tiny size

Housing:	Pressure die-cast aluminum alloy with polyester powder paint
Beam angle:	2.5°, 6°, 9°, 12°, 15°, 20°, 30°, 45°, 60°, 15x60°, 10x70°, 5x20°
Housing color:	Black, Grey, RAL
IES protection classes:	Class I (SELV)
Color temperature:	2700K, 3000K, 4000K, 5000K, 5700K, R, G, B, RGBW 4in1
Input voltage:	36V, 220V
Control system:	On/Off, DMX-512, 0-10V, DALI
Ingress Protection Rating, IP:	IP66
Operating temperature:	-40°C ~ +50°C
Weight, kg:	6.4 kg

Article	Name	Power, W	Dimensions, mm	Input voltage, V	Beam angle, degrees	Color temperature, K	Weight, kg
622201174	GLOWHEAD XXL 100W 220V SINGLE IP66	100W	260x375x325	220V	2.5°, 6°, 12°, 20°, 30°, 45°, 60°, 10x70°, 5x20°	2700K, 3000K, 4000K, 5000K, 5700K, R, G, B	6.4
622201176	GLOWHEAD XXL 120W 220V DMX-512 RGBW IP66	120W	260x375x325	220V	2.5°	RGBW 4in1	6.4
622201178	GLOWHEAD XXL 150W 36V/220V DMX-512 RGBW 4in1 IP66	150W	260x375x325	36V, 220V	9°, 15°, 20°, 30°, 45°, 15x60°	RGBW 4in1	6.4