

TRACKER XL



view



RAL




1 overall dimensions



size

1



TRACKER XL

Multifunctional floodlight for accent lighting

Housing:	Pressure die-cast aluminum alloy with polyester powder paint
Beam angle:	3.5°, 7°, 10°, 12°, 15°, 25°, 40°, 60°, 10°×25°, 15°×35°, 10°×60°
Housing color:	Black, Grey, RAL
IES protection classes:	Class I (SELV)
Color temperature:	3000K, 4000K, 5000K, RGB 3in1, RGBW 4in1
Input voltage:	24V, 220V
Control system:	On/Off, DMX-512
Ingress Protection Rating, IP:	IP66
Operating temperature:	-40°C ~ +50°C
Weight:	7.5 kg

Article	Name	Power	Dimensions, mm	Input voltage	Beam angle	Color temperature	Weight, kg
765120067	TRACKER XL 80W 220V SINGLE IP66	80W	285×357×115	24V, 220V	3,5°	3000K, 4000K, 5000K	7.5
765120069	TRACKER XL 80W 220V RGB3in1 IP66	80W	285×357×115	24V, 220V	3,5°	RGB	7.5
765120071	TRACKER XL 80W 220V RGBW4in1 IP66	80W	285×357×115	24V, 220V	3,5°	RGBW	7.5
765120073	TRACKER XL 100W 220V SINGLE IP66	100W	285×357×115	24V, 220V	7°, 15°, 25°, 40°, 60°, 15°×35°, 10°×60°	3000K, 4000K, 5000K	7.5
765120075	TRACKER XL 100W 220V RGB3in1 IP66	100W	285×357×115	24V, 220V	10°, 12°, 25°, 40°, 60°, 10°×25°, 10°×60°	RGB	7.5
765120077	TRACKER XL 100W 220V RGBW4in1 IP66	100W	285×357×115	24V, 220V	10°, 12°, 25°, 40°, 60°, 10°×25°, 10°×60°	RGBW	7.5
765120079	TRACKER XL 120W 220V SINGLE IP66	120W	285×357×115	24V, 220V	7°, 15°, 25°, 40°, 60°, 15°×35°, 10°×60°	3000K, 4000K, 5000K	7.5
765120081	TRACKER XL 120W 220V RGB3in1 IP66	120W	285×357×115	24V, 220V	10°, 12°, 25°, 40°, 60°, 10°×25°, 10°×60°	RGB	7.5
765120083	TRACKER XL 120W 220V RGBW4in1 IP66	120W	285×357×115	24V, 220V	10°, 12°, 25°, 40°, 60°, 10°×25°, 10°×60°	RGBW	7.5
765120085	TRACKER XL 150W 220V SINGLE IP66	150W	285×357×115	24V, 220V	7°, 15°, 25°, 40°, 60°, 15°×35°, 10°×60°	3000K, 4000K, 5000K	7.5
765120087	TRACKER XL 150W 220V RGB3in1 IP66	150W	285×357×115	24V, 220V	10°, 12°, 25°, 40°, 60°, 10°×25°, 10°×60°	RGB	7.5
765120089	TRACKER XL 150W 220V RGBW4in1 IP66	150W	285×357×115	24V, 220V	10°, 12°, 25°, 40°, 60°, 10°×25°, 10°×60°	RGBW	7.5